


Declaration of Performance Ident.- N°:		01-511-39-1-4/1
JUWÖ Poroton-Werke Ernst Jungk & Sohn GmbH D-55597 Wöllstein		
2016		
2510-CPR-366		
EN 771-1 : 2015		
LD vertically perforated clay masonry unit, Category 1		
498 x 115 x 238 mm		
Intended use: Clay masonry unit for loadbearing and non-loadbearing protected masonry		
Dimensional tolerance (mm)	Mean value Tm (mm)	Length: -10, +8
		Width: -10, +5
		Height: ± 5
	Range: Rm (mm)	Length: 12
		Width: 10
		Height: 6
Flatness of bed faces mm	NPD	
Plane parallelism of bed faces mm	NPD	
Configuration	Z-17.1-1038	
Compressive strength (Mean Value) N/mm ²	≥ 12,5	
Gross dry density (Mean value) kg/m ³	760	
Gross dry density (Range Dm) kg/m ³	660 - 850	
Net dry density (Mean value) kg/m ³	NPD	
Thermal conductivity lambda (W/mK)	NPD see additional manufacturer's information	
Durability against freeze/thaw	F0	
Shear Bond Strength (Tabled values acc.to DIN EN 998-2, Annex. C) N/mm ²	NPD	
Active soluble salts content	Class SO	
Reaction to fire	Class A1	
Water vapour permeability t μ	5 / 10	



F-0030


ThermoBlock HLZ P 511 T λ 0,28 W/(mK)

Additional manufacturer's information



According approval Z-17.1-1038

Product type	ThermoBlock HLZ
Article N°	F-0030
Article name	P 511 T
Compressive strength (class)	12
Class of gross density kg/dm ³	0,8
Thermal Conductivity lambda W/(mK)	0,28
Permitted Compressive Stress - refer to General Building Approval	
Initial rate of water absorption	NPD

DECLARATION OF PERFORMANCE (DOP)				
01-511-39-1-4/1				
1. LD vertically perforated clay masonry unit, Category 1 498 x 115 x 238 mm	9. Declared performance			
	Essential characteristics	Performance	Harmonised technical specification	
2. Article F-0030	Work size LxBxH (mm)	498 115 238	EN 771-1	
3. Clay masonry unit for loadbearing and non-loadbearing protected masonry	Dimensional tolerance (mm)	Mean value Tm (mm)		L: -10, +8 B: -10, +5
		Range: Rm (mm)		H: ± 5
				L: 12 B: 10
4. JUWÖ Poroton-Werke Ernst Jungk & Sohn GmbH Ziegelhüttenstr. 40 - 42 D-55597 Wöllstein	Configuration	Z-17.1-1038	EN 777-1	
	Compressive strength	Category: LD vertically perforated clay masonry unit, Category 1 Mean value: ≥ 12,5 N/mm ² Direction of load: Vertical to the horizontal joint		
5. Not applicable	Moisture movement	NPD	EN 777-1	
	Flatness of bed faces mm	NPD		
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V: System 2+	Plane parallelism of bed faces mm	NPD	EN 777-1	
	Active soluble salts content	Class SO		
	Reaction to fire	Class A1		
	Water absorption (% by mass)	NPD		
7. Notified production control certification body No. CPR/1794 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control	Water vapour permeability t μ	5 / 10	EN 1745	
	Gross dry density	Mean value (kg/m ³)	760	EN 777-1
		Tolerance category Dm (kg/m ³)	660 - 850	
8. Not applicable	Net dry density (Mean value) kg/m ³	NPD	EN 1745	
	Thermal conductivity lambda (W/mK)	NPD see additional manufacturer's information		
	Durability against freeze/thaw / Shear Bond Strength (Tabled values acc.to DIN EN 998-2, Annex. C) N/mm ²	F0 / NPD		
10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4. Signed for and on beh	Dangerous substances	According to ZA.3	<p>Wöllstein, 01.06.2017</p>  <p>Stefan Jungk (Managing director)</p>	